

DECLARATION OF PERFORMANCE – No. 003

Reference to 2412-CPR-1026, in compliance with 305/2011/EU

PRODUCT-TYPE	Fire retardant treated solid wood panels and claddings
INTENDED USE	Cladding in external applications. Horizontal and vertical joints. Any end use substrate of Euroclasses A1 or A2-s1,d0 ≥ 9mm, density ≥ 652 kg/m ³ or any end use substrate of Euroclasses A1 or A2-s1,d0 ≥ 12mm, density ≥ 525 kg/m ³
NAME AND ADDRESS OF THE MANUFACTURER	Holzimprägnierwerk AG, St. Pelagibergstrasse 34, 9205 Waldkirch info@holzimpraegnierwerk.ch, www.holzimpraegnierwerk.ch
SYSTEM OF ASSESMENT AND VERIFICATION OF CONSTANCY OF PERFORMANCE	AVCP-System 1
CONSTRUCTION PRODUCT COVERED BY A HARMONIZED STANDARD	Finotrol Oy, notified certification body no: 2412 has performed initial inspection of the manufacturing plant and production control and performs continuous surveillance, assessment and evaluation of factory production control under system 1 and issued the certificate of conformity of factory production control: 2412-CPR-1026.

DECLARED PERFORMANCE ACCORDING TO HARMONISED TECHNICAL SPECIFICATION EN 14915:2013

Wood species	Density	Thickness	Uptake	Reaction to fire	Air Gap	Durability class
Eiche (Quercus)	500 - 750 kg/m ³	≥ 20 mm	16 kg/m ³	B-s1,d0	-	1
Accoya (Pinus Radiata)	500 - 550 kg/m ³	≥ 19 mm	78 kg/m ³	B-s1,d0	-	1

TREATED AGAINST FIRE

NAME OF TREATMENT CHEMICAL

Burnblock®

RELEASE OF DANGEROUS SUBSTANCES

-



BURNBLOCK®
NATURAL & NON-TOXIC FIRE RETARDANT

Signed by manufacturer, 10.12.2021

Paul Scheiwiller, Owner & CEO
Holzimprägnierwerk AG, Waldkirch

Aaron Scheiwiller, Quality Control
Holzimprägnierwerk AG, Waldkirch



Holzimprägnierwerk | Waldkirch

St. Pelagibergstrasse 34 | CH-9205 Waldkirch | +41 71 433 10 33
info@holzimpraegnierwerk.ch | holzimpraegnierwerk.ch

