

# DECLARATION OF PERFORMANCE – No. 004

Reference to 2412-CPR-1026, in compliance with 305/2011/EU

<b>PRODUCT-TYPE</b>	Fire retardant treated wood-based panels for use in construction and claddings
<b>INTENDED USE</b>	Cladding in external applications. Horizontal and vertical joints. Any end use substrate of Euroclasses A1 or A2-s1,d0 ≥ 9mm, density ≥ 652 kg/m <sup>3</sup> or any end use substrate of Euroclasses A1 or A2-s1,d0 ≥ 12mm, density ≥ 525 kg/m <sup>3</sup>
<b>NAME AND ADDRESS OF THE MANUFACTURER</b>	Holzimprägnierwerk AG, St. Pelagibergstrasse 34, 9205 Waldkirch info@holzimpraegnierwerk.ch, www.holzimpraegnierwerk.ch
<b>SYSTEM OF ASSESMENT AND VERIFICATION OF CONSTANCY OF PERFORMANCE</b>	AVCP-System 1
<b>CONSTRUCTION PRODUCT COVERED BY A HARMONIZED STANDARD</b>	Finotrol Oy, notified certification body no: 2412 has performed initial inspection of the manufacturing plant and production control and performs continuous surveillance, assessment and evaluation of factory production control under system 1 and issued the certificate of conformity of factory production control: 2412-CPR-1026.

## DECLARED PERFORMANCE ACCORDING TO HARMONISED TECHNICAL SPECIFICATION EN 14915:2013

Wood species	Density	Thickness	Uptake	Reaction to fire	Air Gap	Durability class
Birch (Betula)	745 kg/m <sup>3</sup>	12 mm	50 kg/m <sup>3</sup>	B-s1,d0	40 mm	2
	722 kg/m <sup>3</sup>	6.5 mm	20 kg/m <sup>3</sup>	C-s1,d0	-	
Pine (Pinus sylvestris)	684 kg/m <sup>3</sup>	12 mm	60 kg/m <sup>3</sup>	B-s1,d0	40 mm	1

## TREATED AGAINST FIRE

**NAME OF TREATMENT CHEMICAL** Burnblock®  
**RELEASE OF DANGEROUS SUBSTANCES** -



**BURNBLOCK®**  
NATURAL & NON-TOXIC FIRE RETARDANT

Signed by manufacturer, 10.12.2021

**Paul Scheiwiller**, Owner & CEO  
Holzimprägnierwerk AG, Waldkirch

**Aaron Scheiwiller**, Quality Control  
Holzimprägnierwerk AG, Waldkirch



**Holzimprägnierwerk** | Waldkirch

St. Pelagibergstrasse 34 | CH-9205 Waldkirch | +41 71 433 10 33  
info@holzimpraegnierwerk.ch | holzimpraegnierwerk.ch

